Elitfönster

DoP Original Alu 100, ADC,61-29-CE1031001en

Declaration of Performance:

Product:	ADC
GTIN	7320930201524
Size:	1230/2180
Manufacturer:	Inwido Sverige AB, Brogårdsgatan 1, 574 38 Vetlanda
Intended use:	Windows for fitting verticaly in domnestic and commercial buildings
System of assassement and verification of constancy of performance:	System 3
Harmonmized standard:	SS-EN 14351-1:2006+A2:2016
Notified body:	RISE id nr 0402, ift Rosenheim id nr 0757

Performance	Essential properties, Performance
Watertightness:	E1050
Dangerous substances:	NPD
Resistance to wind load:	4C
Load-bearing capatity of safety devices:	Approved
Accustic performance:	34 dB (-2;-6)
Thermal transmittance:	1,0
Air permability:	4
Air permability:	4

Radiation properties

Light transmittance (LT):	0,75
Solar factor (g):	0,6

The performance of the product is consistent with the specified performance. This declaration of performance has been issued in accordance with Regulation (EU) No 305/2011 at the sole responsibility of the manufacturer specified above.

Signed on befalf of the manufacturer:

Name:	Viktor Arvidsson
Date:	2024-04-01
City:	Vetlanda