

## DoP Inåtg 2+1 UKH (IKIU-AL), 40-29-CE3035101-en

Doc	laration	of Por	formance:

Product:	Inåtg 2+1 UKH (IKIU-AL)

Size: 1480/980

Manufacturer: Inwido Sverige AB, Brogårdsgatan 1, 574 38 Vetlanda

Intended use: Windows for fitting vertically in domnestic and commercial buildings

System of assassement and verification of constancy of

performance:

System 3

Harmonmized standard: SS-EN 14351-1:2006+A2:2016

Notified body: RISE id nr 0402, ift Rosenheim id nr 0757

## Performance Essential properties, Performance

Watertightness: E1200

Dangerous substances: NPD

Resistance to wind load: 4C

Load-bearing capatity of safety devices: Approved

Accustic performance: 43 dB (-2;-6)

Thermal transmittance: 1,1

Air permability: 4

## **Radiation properties**

Light transmittance (LT):	0,75
Solar factor (g):	0,6

The performance of the product is consistent with the specified performance.

This declaration of performance has been issued in accordance with Regulation (EU) No 305/2011 at the sole responsibility of the manufacturer specified above.

Signed on befalf of the manufacturer:

Name: Viktor Arvidsson

Date: 2022-02-01

City: Vetlanda