

DoP Original Trä Objekt 100, EDO2 filling,61-29-CE1030902-2f-en

Dec	laration	of Peri	formance	٠

Product:	EDO2 filling	
GTIN	7320930201463	
Size:	1780/2180	
Manufacturer:	Inwido Sverige AB, Brogårdsgatan 1, 574 38 Vetlanda	
Intended use:	Windows for fitting verticaly in domnestic and commercial buildings	
System of assassement and verification of constancy of performance:	System 3	
Harmonmized standard:	SS-EN 14351-1:2006+A2:2016	
Notified body:	RISE id nr 0402	

Performance	Essential properties, Performance				
Watertightness:	9A				
Dangerous substances:	NPD				
Resistance to wind load:	3C				
Load-bearing capatity of safety devices:	Approved				
Accustic performance:	NPD				
Thermal transmittance:	1,2				
Air permability:	4				
Dediction was well a					
Radiation properties					
Light transmittance (LT):	0,75				

The performance of the product is consistent with the specified performance.

This declaration of performance has been issued in accordance with Regulation (EU) No 305/2011 at the sole responsibility of the manufacturer specified above.

0,6

Signed	on	hefalf	of the	manufacturer:

Solar factor (g):

Name: Viktor Arvidsson

Date: 2024-01-01

City: Vetlanda