

Declaration of performance ETIDL-AL filling,40-29-UKCA3046101f

Dec	laration	of	Perfo	rmance:	•

Product:	ETIDL-AL filling
GTIN	7320930201302
Size:	980/2080
Manufacturer:	Inwido Sverige AB, Brogårdsgatan 1, 574 38 Vetlanda
Intended use:	Windows without fire resistance or flue gas leakage properties for installation in homes or premises.
System of assassement and verification of constancy of performance:	System 3
Harmonmized standard:	BS EN 14351-1:2006+A2:2016
Notified body:	RISE id nr 0402, ift Rosenheim id nr 0757

Performance	Essential properties, Performance
-------------	-----------------------------------

	zecentiai properties, i errermanee	
Water resistance (class):	E1050	
Dangerous substances:	NPD	
Resistance to wind load (class):	4C	
Carrying capacity of safety devices:	Approved	
Sound insulation:	27 dB (-3;-3)	
U-value:	NPD	
Airtightness (class):	4	

Radiation properties

Lighttransmission (LT):	0,75
g-value (g):	0,6

The performance of the above product is consistent with the stated performance.

This declaration of performance has been issued in accordance with Construction products regulation in Great Britain under the sole responsibility of the manufacturer specified above.

Signed on befalf of the manufacturer:

Name: Viktor Arvidsson

Date: 2024-11-01

City: Vetlanda